

QN-B002

**1/2" Super High Sensitive
B&W CCD Camera**

Minus 0.00000001 Lux



Technical Specifications

| | |
|--------------------------|--|
| System: | EIA / CCIR |
| Pick Up Element: | 1/2" Interline CCD |
| Picture Elements: | EIA: 811(H) x 508(V) / CCIR: 795(H) x 596(V) |
| Scanning System: | 2.1 Interlaced |
| H Drive Frequency: | EIA: 15.734 KHz / CCIR: 15.625 KHz |
| V Drive Frequency: | EIA: 59.9 Hz / CCIR: 50.0 Hz |
| Sync System: | Internal |
| Horizontal Resolution: | More than 570 TV Lines |
| Min. Illumination: | 0.00000001 Lux |
| S / N Ratio: | More than 50dB (AGC ON) |
| Gamma: | 0.45 |
| Lens Mount: | CS |
| AGC: | ON, OFF, HIGH, MIDDLE, LOW |
| Video Out: | 1.0 Vp-p 75 ohm |
| Back Light Compensation: | SELECTABLE |
| Auto Iris: | DC and video type |
| Electric Iris: | EIA: 4(slow shutter max.) - 1/100,000 CCIR: 5 (slow shutter max.) - 1/100,000 |
| Shutter Speed: | X256, x128, x64, x32, x16, x8, x4, x2 1/60(50), FLK, 1/250, 1/500, 1/2,000, 1/5000, 1/10,000, 1/100,000 |
| Power: | DC 12V ± 10% |
| Current: | Less than 180mA |
| Operational Temperature: | -10°C ~ +40°C |
| Dimensions: | 34mm (V) x 35.5mm (H) x 63.6mm (D) or less |
| Weight: | 80g |

