

QN-B808ET



1/3" CCD BLACK & WHITE BOARD

EIA CCIR



HIGH RESOLUTION

> 570 TV LINES

EXTERNAL SYNC SYSTEM

- Backlight Compensation
- Infra Red Light Response

HIGH SENSITIVITY

> 0.0003 LUX

MODEL	EIA	CCIR
PICK-UP DEVICE	1/3" CCD	
TOTAL PIXELS	811(H) X 508(V)	795(H) X 596(V)
EFFECTIVE PIXELS	768(H) X 494(V)	752(H) X 582(V)
LENS MOUNT	CS MOUNT	
SYNC SYSTEM	EXTERNAL	
SCANNING SYSTEM	2 : 1 INTERLACE	
VIDEO OUT	1 Vp-p 75 Ohm	
H RESOLUTION	> 570 TV LINES	
MINIMUM ILLUMINATION	0.0003 LUX F1.2 (AGC HI) / 0.005 LUX F1.2 (AGC LOW)	
S/N RATIO	> 50 dB (AGC OFF)	
ELECTRIC IRIS	NON LIMIT : 1/60(EIA)1/50(CCIR) ~ 1/100,000 LIMIT ON : 1/100(EIA)1/120(CCIR) ~ 1/100,000	
SHUTTER SPEED	SELECTABLE EIA : 1/100, 1/250, 1/500, 1/1000, 1/2000, 1/5000, 1/10000, 1/100000 CCIR : 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/5000, 1/10000, 1/100000	
GAMMA	0.45 / 1.0	
AGC	ON / OFF / HI / LOW SELECTABLE	
BACK LIGHT COMPENSATION	SELECTABLE	
POWER SOURCE	DC +12V±10% 180mA MAX	
STORAGE TEMPERATURE	-30°C ~ +70°C	
OPERATING TEMPERATURE	-10°C ~ +40°C	
DIMENSIONS	42mm(W) X 42mm(H) X 19.7mm(D)	
WEIGHT	25g	

● B808 Internal Sync System Model Is Available Too.

* Design and specification are subject to change without notice.